

Description

This tape consists of a modified dispersion acrylate adhesive which has high temperature, aging and plasticiser resistance.

Carrier

Without carrier

Liner

Brown paper, silicone-coated on both sides, 90 g/m²

Adhesive

APEO free modified dispersion acrylate

Area of use

This tape is suitable for the adhesion of textiles, wood, soft PVC and other lightly structured or stamped surfaces.

Technical Data

Thickness* (adhesive and carrier)	50 micron	
Temperature resistance	-40° C to +140° C	
LoopTack* (FINAT TM 9)	13 N/25 mm	
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	12 N/25 mm	after 1min
	15 N/25 mm	after 20min
	17 N/25 mm	after 24h
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 24 hours	at 23° C
	30 minutes	at 70° C
Temperature resistance* (S.A.F.T.)	110° C	
Shelf life**	1 year	
Application temperature	> +15° C	

* average ** in original packaging, at 20°C and 50% relative humidity

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.