

## Description

This mounting tape consists of a white, closed-cell polyethylene foam coated on both sides with a rubber adhesive. The rubber adhesive adheres well among other things on apolar substrates. The double sided mounting tape is lined with a white silicone paper.

## Carrier

Closed-cell polyethylene foam, white, 1000 micron

## Liner

White paper, both sides coated with silicone, 90 g/m<sup>2</sup>

## Adhesive

Rubber

## Area of use

For fixing of boards, displays and for a variety of household applications. A universal, economical product. Good adhesion also on rough surfaces.

## Technical Data

<b>Thickness*</b> (adhesive + foam)	1100 micron
<b>Density*</b>	58 kg/m <sup>3</sup>
<b>Temperature resistance***</b>	-30° C to +70° C
<b>LoopTack*</b> (FINAT TM 9)	35 N/25 mm
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min: 18 N/25 mm after 20 min: > 18 N/25 mm after 24 h: > 18 N/25 mm
<b>Shear strength*</b> (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	at 23° C: > 500 hours at 70° C: 1 hour
<b>Temperature resistance*</b> (S.A.F.T.)	75° C
<b>Shelf life**</b>	1 year
<b>Application temperature</b>	> +15° C

\* average    \*\* in original packaging, at 20°C and 50% relative humidity    \*\*\* 1h, normal climate of Central Europe

## IMPORTANT NOTICE

All ORAMOUNT® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAMOUNT® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAMOUNT® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAMOUNT® is a registered trademark of ORAFOL Europe GmbH.